

PMX



The PMX is the latest SMG developed by Beretta. The extensive use of polymer materials and light alloy metals allowed the design of a compact, lightweight, yet rugged structure, one which is versatile and easy to deploy in combat. The major components: barrel and bolt, are machined from special high-strength steel, specifically designed to withstand the rigors of harsh environments and abusive conditions. The lightweight and ergonomically designed stock can be folded by simply pushing a button. The oversized magazine release button is positioned on both sides of the sub-machine gun, while the cocking handle can be easily reversed to be comfortably operated from either side. The PMX uses a translucent, lightweight, and yet resistant, 30-round polymer magazine allowing the visual count of the rounds present in the mag. The Beretta PMX is equipped with Picatinny rails (MIL-STD-1913) positioned on top, bottom and on the sides of the receiver.





Configurations

| Caliber | 9x19mm |
|-----------------------------------|---|
| Magazine Capacity | 30 rounds |
| Stock | Foldable |
| Weight Unloaded Empty Magazine | approx. 2,5kg / 88.18oz |
| Rifling Pitch | 250mm / 10in |
| Operating Principle | Blowback |
| Threaded Barrel | Yes |
| Barrel Thread | 1/2" x28 |
| Number of Grooves | R.H 6 grooves |
| Sights System | Flip-up iron sight |
| Lower Receiver Material | Fiberglass reinforced technopolymer |
| Upper Receiver Material | Metal tube overmolded with fiberglass reinforced technopolymer |
| Accessory Rail | MIL-STD-1913 |
| Safeties | Manual safety |
| Fire Selector Positions | Three position S-1-F |
| Reciprocating System | Yes |
| Ejection Side | Right |
| Lenght Min / Max | approx. 418-640mm / 16.46-25.20in |
| Height | approx. 250mm / 9.84in |
| Width | approx. 74mm / 2.91in |
| Barrel Length | approx. 175mm / 6.89in |
| Sight Radius | 250mm / 10in |

